

wolcraft®



Master RT 540

master RT 540



High-quality milling table with many clever details for safe working with the highest precision.

The master RT 540 turns the router into a comfortable stationary device. With its many technical specialities, its versatility is increased even further.

- extremely flat die cast aluminium table top
- table extensions for an increased resting space – also ideal for large work pieces
- router cutter storage – the more important router cutters are always at hand
- integrated safety switch

Art.-Nr. 6156506



Guide fed from both sides together with an integrated adjustable fence on the removal side for a flat positioning both in front of and after the milling.



Connection for dust extraction.



Vertical guide slide for the secure guiding of long work pieces.



Variable push-in feather boards for a uniform pressure and as a form of protection against recoiling.




Table inserts for the secure guiding of small work pieces and as a form of sawdust protection for the router.



Large angle guide for simple and precise guiding.



HSS/HM-milling cutters from wolcraft

The right choice for professional milling

- HSS-milling cutters made of high-speed steel for milling of hard and soft wood as well as plastic.
- CT-milling cutters with hard-metal cutting edges are particularly suitable for milling of hard wood, chipboard, hard fibre board and plastic-coated boards.

Version : 6 mm shank = Art.-Nr.: 38.....
8 mm shank = Art.-Nr.: 39.....



Straight bit

3800 000 HSS Ø 4 x 14 mm
3801 000 HSS Ø 5 x 14 mm
3802 000 HSS Ø 6 x 17 mm
3803 000 HSS Ø 8 x 20 mm
3804 000 HSS Ø 10 x 20 mm
3824 000 HM Ø 6 x 19 mm
3825 000 HM Ø 8 x 20 mm
3826 000 HM Ø 10 x 20 mm
3827 000 HM Ø 12 x 20 mm
3822 000 HM Ø 14 x 20 mm



Core box bit

3807 000 HSS Ø 12 x 12 mm,
r = 6 mm
3967 000 HM Ø 13 x 9,5 mm,
r = 6,4 mm



Round over bit with guide pin
3863/3863 000 HM Ø 25 x 12,7 mm
r = 6,35 mm




V-groove bit

3806 000 HSS Ø 12 mm, 60°



Chamfering bit with guide pin
3872/3972 000 HM Ø 29 x 15,7 mm,
45°



Straight face bit

without shank:
3828 000 HM Ø 40 x 3 mm
3829 000 HM Ø 40 x 4 mm
3830 000 HM Ø 40 x 5 mm
3831 000 shank 6 mm
3831 000 shank 8 mm



Coving bit

with guide pin
3871/3971 000 HM Ø 22 x 12,7 mm
r = 6,35 mm



Chamfering bit

3816 000 HSS Ø 25 x 13 mm
45°

www.wolcraft.de

Ⓒ **wolcraft® Ltd.**

The Granary
Walnut Tree Lane
Sudbury
Suffolk CO10 1BD
Tel. 00 44 (0) 17 87 88 07 76
Fax 00 44 (0) 17 87 31 03 67

Ⓒ **wolcraft® Middle East Ltd.**

P.O. Box 2428
IL-Jerusalem
Tel. 9 72 (2) 6 52 60 24
Fax 9 72 (2) 6 52 95 13
Handy 9 72 (50) 52 06 49
womea@netvision.net.il
www.Wolcraft.co.il

Ⓒ **DONG-JIN Jaeseok Co. LTD.**

811-2, Bangbae - 4 Dong
Seocho - Gu
KOREA
Tel. 00 82 2 5 99 28 33
Fax 00 82 2 5 95 75 90
knkim@wolcraft.co.kr

Ⓒ **wolcraft® GmbH**

Wolff-Strasse
D-56746 Kempenich
Tel. 00 49 (0) 26 55 51 0
Fax 00 49 (0) 26 55 51 1 80
customerservice@wolcraft.com
Service-Hotline: 0 180-5 32 94 68

9925 566 / 03.03

